

711.07831 REV 16 – OneView/ClearView Camera PC System (no In-Situ)

Manufacturer: Dell
Model: Precision T7920 XL (711.07830 Rev 14)

Base Unit:	Precision 7920 XL Tower Workstation (210-AMRP, 321-BGVL, 329-BBJL, 389-CGHR)
Processor:	(2) Intel Xeon Gold 6230R, 26 cores, 2.1 GHz, 35.75 Mb L3 cache, 10.4 GT/s, 150W, 4.0 GHz Turbo, air heat pipe (338-BWPV, 338-BWSW, 575-BBPB, 412-AALD, 412-AALE)
Memory:	128 Gb, DDR4 RDIMM, 2933 MHz, ECC; (4) 32 Gb DIMMs see Note 6
Video Card:	(1) nVidia T1000, 4 Gb GDDR6, 896 CUDA Cores, PCIe v3 x16, 50W with (4) mDP v1.4 connections, (4) mDP to DP adapters (490-BGXV)
Monitor:	(1) Dell 32" Widescreen flat panel display, P3223QE, 3840x2160, HDMI/DP & USB-C hub connections, 2m DP-DP cable, 3 years Advanced Exchange Service (210-BDQC, 844-1960, 844-1966)
HD Configuration:	Intel NVMe PCIe SSD, Front PCIe FlexBay (414-BBBV, 411-XXYB)
Hard Drives:	(1) 1 Tb, NVMe, Class 40, Solid State, M.2 form factor (401-ABJR, 400-AVDR)
HD RAID:	no RAID 0 (780-BBCJ)
HD Controller:	Intel Integrated RST-e for front FlexBay NVMe drives (321-BDFD, 321-BDFE)
Optical Drive:	8x DVD +/-RW, Slimline, SATA (325-BCTX, 429-ABDW, 658-BBTB)
Power Supply:	1400 W, 90% efficiency (470-AATC)
Energy Efficiency:	Energy Star (387-BBMV)
Operating System:	Windows 11 Pro for Workstations, 64-Bit, 6 cores plus, English (619-AQLO, 620-AALW) see Note 1
Network Adapter:	Integrated Intel (1) i219 & (1) i210 Gigabit Ethernet controllers (555-BBJO)
Keyboard:	US English (QWERTY), KB216, wired USB, black (580-ADJC)
Mouse:	MS116 Optical LED tracking, wired USB, 2 buttons, scroll wheel, black (570-ABIE)
Speakers:	Internal
System Recovery:	Precision Resource DVD (430-XYMF)
Expansion Slots:	1 PCIe x8, Gen 3, open ended connector, CPU 0 2 PCIe x16, Gen 3, 75W, CPU 0 (occupied by Video card) 3 PCIe x16, Gen 3, wired as x1, CPU 0 4 PCIe x16, Gen 3, 75W, CPU 0 5 PCIe x16, Gen 3, wired as x4, can accommodate double width card, CPU 0 6 PCIe x16, Gen 3, 75W, can accommodate double width card, CPU 1 7 PCIe x16, Gen 3, 75W, CPU 1
I/O Ports:	Front: (2) USB 3.1 Type A, (2) USB 3.1 Type C, (1) universal audio, (1) SD Rear: (6) USB 3.1 Type A, (2) RJ45, (1) PS/2 keyboard, (1) PS/2 mouse, (1) Serial, (1) Audio line-in, (1) Audio line-out
Service:	3 years ProSupport with NBD Onsite Service (989-3449, 997-5852, 997-5877, 997-5893)
Documentation:	Safety/Environment and Regulatory Guide (340-AGIK) Placemat 7920 Tower (340-BVYE)

Notes:

- Support for Windows 11 begins with GMS software version 3.6.0.
- If the specific hardware device configuration requires more expansion slots than what is available on the motherboard, an Expansion Enclosure System will also need to be purchased. Reference **Gatan p/n# 101780** (StarTech #PEX2PCIE4L)
- If the monitor, keyboard and mouse need to be located farther from the computer than would be permitted by the standard 2m cabling, an optional 10m Ultra HD monitor cable bundle may be purchased (**included if computer purchased from Gatan**). Reference **Gatan p/n# 711.27000**
- When purchased from Gatan, this system is also provided with (1) USB 3 to RJ45 Gigabit Ethernet adapter. Reference **Gatan p/n# 106582**
- When purchased from Gatan, this system is also provided with (1) USB A female to USB B female adapter. **Gatan p/n# 109295**
- Note that if a OneView camera T7920 PC that has been delivered to a Customer is to be retro fitted with a ClearView camera in the field, the existing 32 GB of memory will need to be upgraded to 128 GB. Reference **Gatan p/n# 711.07833**

Important: Check with the Software group and Marketing before changing this specification.