



## 711.07861 REV 10 – Rio Camera PC System (no In-Situ)

Manufacturer:

Dell

Model:

Precision T7920 XL

Base Unit:	Precision 7920 XL Tower Workstation (210-AMRP, 321-BFVF, 329-BBJL, 389-CGHR)
Processor:	(2) Intel Xeon Gold 5218, 16 core, 2.3 GHz up to 3.7 GHz Turbo, 22 MB L3, 10.4 GT/s, 125W (338-BSQG, 338-BSRP, 575-BBPB, 412-AALD, 412-AALE)
Memory:	32 Gb, DDR4 RDIMM, 2666 MHz, ECC; (4) 8 Gb DIMMs (370-ADTK)
Video Card:	(1) nVidia Quadro T600, 4 Gb GDDR6, 640 CUDA Cores, PCIe v3 x16, 40 W max power consumption, (4) mDP v1.4 connectors, (4) mDP to DP adapters (490-BGXZ)
Monitor:	(1) 32" Widescreen flat panel Ultra HD display, 3840x2160, HDMI/DP connections, 2m DP-DP cable, 3 years Advanced Exchange Service: <b>U3219Q</b> (210-AQZZ, 827-0203, 827-0214) <b>or P3222QE</b> (210-BBCQ, 844-1960, 844-1966), also include USB-A (f) to USB-B (f) adapter
HD Configuration:	Intel NVMe PCIe SSD, Front PCIe FlexBay (414-BBBV, 411-XXYB)
Hard Drives:	(2) 256 Gb, NVMe, Class 40, Solid State, M.2 form factor (401-ABJS, 400-AVDR)
HD RAID:	Intel VROC, RAID 0, (1) 512 Gb logical drive (780-BCIJ, 780-BCIP)
HD Controller:	Intel Integrated RST-e for front FlexBay NVMe drives (321-BDFD, 321-BDFE)
Optical Drive:	8x DVD -/+RW, Slimline, SATA (325-BCTX, 429-ABDW, 658-BBTV)
Power Supply:	1400 W, 90% efficiency (470-AATC)
Energy Efficiency:	Energy Star (387-BBMV)
Operating System:	Windows 10 Professional for Workstations, 64-Bit, 6 cores plus, English (619-APRU)
Network Adapter:	Integrated Intel (1) i219 & (1) i210 Gigabit Ethernet controllers
Keyboard:	US English (QWERTY), KB216, wired USB, black (580-ADJC)
Mouse:	MS116 Optical LED tracking, wired USB, 2 buttons, scroll wheel, black (570-ABIE)
Speakers:	Internal
System Recovery:	Windows 10 media not included (620-AALW) Precision Resource DVD (430-XYMF)
Expansion Slots:	1 PCIe x8, Gen 3, open ended connector, CPU 0 2 PCIe x16, Gen 3, 75W, CPU 0 (occupied by Video card) 3 PCIe x16, Gen 3, wired as x1, CPU 0 4 PCIe x16, Gen 3, 75W, CPU 0 5 PCIe x16, Gen 3, wired as x4, can accommodate double width card, CPU 0 6 PCIe x16, Gen 3, 75W, can accommodate double width card, CPU 1 7 PCIe x16, Gen 3, 75W, CPU 1
I/O Ports:	Front: (2) USB 3.1 Type A, (2) USB 3.1 Type C, (1) universal audio, (1) SD Rear: (6) USB 3.1 Type A, (2) RJ45, (1) PS/2 keyboard, (1) PS/2 mouse, (1) Serial, (1) Audio line-in, (1) Audio line-out
Service:	3 years ProSupport with NBD Onsite Service (989-3449, 997-5852, 997-5877, 997-5893)
Documentation:	Safety/Environment and Regulatory Guide (340-AGIK) Placemat 7920 Tower (340-BVYE)

### Notes:

1. GMS software version 3.2.0 (or newer) is required for support of acquisition equipment in the Windows 10 environment.
2. If the specific hardware device configuration requires more expansion slots than what is available on the motherboard, an Expansion Enclosure System will also need to be purchased. Reference Gatan p/n# 101780 (StarTech #PEX2PCIE4L)
3. If the monitor, keyboard and mouse need to be located farther from the computer than would be permitted by the standard 2m cabling, an optional 10m Ultra HD monitor cable bundle may be purchased (**included if computer purchased from Gatan**). Reference Gatan p/n# 711.27000
4. When purchased from Gatan, this system is also provided with (1) USB 3 to RJ45 Gigabit Ethernet adapter. Reference Gatan p/n# 106582

**Important:** Check with the Software group and Marketing before changing this specification.